

AENEON
Simply advanced

Unbuffered Memory Module
Data Sheet

AET760UD00-370

1 GByte DDR2–533 CL4 240-Pin UDIMM

Description

This data sheet describes features and specification of AENEON memory module family AET760UD00-370. The four digit product type postfix is for internal logistic purposes.

Features

- 1 GByte organized as 128 M × 64 bit
- Double Data Rate Two SDRAM components
- Speed grade DDR2–533 CL4 on component level
- Provides up to 4264 MByte per second on module level
- Module Code PC2–4200U–444–11
- 240-Pin Dual Inline Memory Module (DIMM) with gold contacts
- Fitting in industry standard motherboards

Specification

Parameter	Values
Clock cycle time t_{CK} for CL4	3.75 ns (min.) / 8 ns (max.)
Clock cycle time t_{CK} for CL3	5 ns (min.) / 8 ns (max.)
Row cycle time t_{RC}	60 ns (min.)
Refresh row cycle time t_{RFC}	127.5 ns (min.)
Activate to read/write delay t_{RCD}	15 ns (min.)
Row active time t_{RAS}	45 ns (min.) / 70.000 ns (max.)
Single power supply $V_{DD} = V_{DDQ}$	1.8 V ± 0.1 V
Operating power I_{DD0}	2.3 W (max.)
Module dimensions L x W x H	133.35 mm x 30.0 mm x 4.0 mm (max.)
	5.25" x 1.18" x 0.16" (max.)

All Rights Reserved.

Attention please!
The information herein is given to describe certain components and shall not be considered as a guarantee of characteristics. Terms of delivery and rights to technical change reserved. We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Warnings
Under no circumstances may Infineon Technologies products of the brand AENEON ("Aeneon Product(s)") be used in any applications, devices or systems that are safety critical or serve the purpose of supporting, maintaining, sustaining or protecting human life (such applications, devices and systems collectively referred to as "Critical Systems"), if

1. A failure of the AENEON Products can reasonable be expected to –directly or indirectly–
   a. Have a detrimental effect on such Critical Systems in terms of reliability, effectiveness or safety; or
   b. Cause the failure of such Critical Systems; or
2. A failure or malfunction of such Critical Systems can reasonably be expected to –directly or indirectly–
   a. Endanger the health or the life of the user of such Critical Systems or any other person; or
   b. Otherwise cause material damages (including but not limited to damages or serious injury to life or property, whether tangible or intangible).